

## XRC 150-165

### X-RAY CONTROL SYSTEM

## PALLET AND CARGO



SecurSCAN XRC 150-165 is a large X-ray security system, specific for scanning pallets of goods and packaging, even very heavy ones. It allows the identification of **organic and inorganic materials** including counterfeit objects, contraband, weapons of all kinds, artisanal and conventional **explosive devices (IED)**, **liquid, solid, powdered drugs**.

The nature of the materials that make up the scanned objects is represented by a predetermined color code:

**organic materials in orange, metallic materials in blue, inorganic materials in green and non-penetrable materials in black.**

The representation of the baggage is **without shadow areas**, and it is possible to automatically signal in real time (with a moving belt) the presence of **dangerous objects** (guns, knives, hacksaws, etc.) with a settable threshold.

#### PHYSICAL PROPERTIES

Tunnel Dimensions:	153 x 165.5 cm. (WxH)
Overall Size:	644.5x244x214.5 cm. (WxLxH)
Total Weight:	2.450 kg.
Conveyor Height:	29.5 cm.
Conveyor Load Capacity:	3.000 kg. Evenly Distributed
Conveyor Speed:	0,20 mt/sec.
System Power:	230VAC +/- 10% / 60-50 Hz

#### STANDARD FEATURES

- Programmable Function Keys
- Parcel Counter
- Date and Time Display
- Virtual Threat Image Projection (TIP)
- Organic/Inorganic Threat Alarm
- Operator Training Program (OTP)
- Self Diagnosis
- Generator Timer
- Automatic Stop Conveyor

#### MAIN FIELDS OF APPLICATION

XRC 150-165 is suitable for the meticulous control of pallets of goods and heavy packaging, not exceeding cm. 150x165, in areas with high freight traffic such as:

- Customs
- Logistic Warehouses
- Depot and Storage Centers
- Goods sorting centers
- Airports and Terminals

# XRC 150-165

## X-RAY CONTROL SYSTEM

## PALLET AND CARGO

### X-RAY GENERATOR & IMAGE PERFORMANCE

Steel Penetration:	50 mm guaranteed; 52 mm typical
Wire Resolution:	36 AWG guaranteed; 38 AWG typical
Anode Voltage:	200 kV, operating at 200 kV
Tube Current:	1,2 mA
Beam Direction:	Vertically upward
Cooling:	Oil and forced air cooling

### COMPUTER SPECIFICATIONS

Processor:	Intel Core i5 (or superior)
Monitor:	color 24" LED
Memory:	4GB RAM min.
Video Card:	2GB min.
Hard Drive:	1TB min.
USB Port:	6 ports min.
Operating System:	Linux

### OPERATING ENVIRONMENT

Operating Temperature:	-20° > 50° C
Storage Temperature:	-20° > 50° C
Relative Umidity:	10% > 90% non condensing

### OPTIONAL ACCESSORIES

- External UPS (For system)
- Operator Console (Open-Closed/Adjustable/I-stand)
- 21,5" - 27" Flat Monitor
- Input / Output Rollers
- Test Kit (STP/ASTM)
- Protective Cover
- Search Table
- Tray Return System (Motorized/Gravity)
- Inclined Conveyor
- Ultrasonic Rat Repellent
- Radiation Meter

### HEALTH AND SAFETY

#### HEALTH AND SAFETY

All SecurSCAN X-Ray products meet all applicable international health and safety regulations.

US FDA Federal Standard 21CFR 1020.40

Health and Safety at Work Act 1974-compliant 6: Available

Film Safety: ISO 1600 / 33 DIN

CE Compliance: Certified

FCC & IEC Compatibility: Available

IP 20 Safety: Certified

Maximum level of radiation the exterior panels come in contact with is 0.1 mR/hour

### STANDARD IMAGE PROCESSING FEATURES

- Perfect View (Detail Enhancement) (PV)
- Edge Enhancement (EE)
- Pseudo Color (PS)
- Organic Materials (OM)
- Inorganic Materials (IM)
- Black & White (B/W)
- Inverse Colors (IN)
- High Penetration (HP)
- Variable Edge Enhancement (+E -E)
- Variable Density (+D -D)
- Variable Gamma (+G -G)
- Variable Color Separation (+C -C)
- Zoom (64x)
- Sniper Zoom
- Recall Previous Images
- Manual/Automatic Archive
- Annotated Archive
- Multi Energy Viewer (4 - 6 Color)
- Atomic Number Display (Z Value)

### OPTIONAL FEATURES

- Barcode Reader System
- External Camera Archiving
- Remote Viewing Station
- Recheck Station
- Network Supervisory System (NSS)
- Remote Access Connection
- Smart Card Login

